

ViewSonic® LARGE FORMAT DISPLAY **CDE4803**

Key Features

- Integrated USB Multimedia Player
- Free Bundled vController Software
- Hospitality Mode
- Control Multiple Devices
- Enhanced Viewing Comfort



Product Description

The ViewSonic CDE4803 is a great value, high performance 48" Full HD LED commercial display for hotel, restaurant and hospitality environments. In addition to versatile connectivity options, including HDMI, VGA, and SPDIF, the display comes with a simple and convenient USB multimedia playback functionality. With 1920x1080 resolution, 350-nit brightness, wide viewing angles and dual 10W stereo speakers, the slim-bezel CDE4803 delivers vivid images and remarkable sound for superior multimedia performance. The HDMI CEC pass-through support provides one-touch-play, with additional features for multiple connected devices such as HD set-top-boxes, media players, and Blu-ray™ players. An RS232 port with IR pass-through provides automated control for hospitality installation. Creating a more comfortable viewing experience, the display is equipped with Flicker-Free and Blue Light Filter technologies. In addition, free-bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop.

Visit Us ■ www.viewsonic.com

LCD PANEL

Panel Size:	48"
Type / Tech:	TFT LCD Module with WLED Backlight
Display Area:	1054.08 x 592.92 mm
Aspect Ratio:	16:9
Resolution:	1920x1080
Colors:	1.06 Billion Colors
Brightness:	350 nits
Contrast Ratio:	4000:1 (typ.)
Response Time:	8 ms
Viewing Angles:	H = 178, V = 178 (typ.)
Backlight:	LED Backlight
Backlight Life:	30,000 Hours (typ.)
Orientation:	Landscape / Portrait

INPUT

HDMI:	x2
RGB / VGA:	x1
Audio:	x1
RS232:	x1

OUTPUT

Audio:	x1
SPDIF:	x1
IR Pass Through:	x1

USB

Type A:	x1
---------	----

SPEAKERS

10W x 2

COMPATIBILITY

RGB PC/HDMI PC:	Up to 1920x1080 @60Hz.
HDMI:	480i, 480p,720p, up to 1080p

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	"On": Max 149 W, 115 W(Default) "Off"(Suspend): ≤ 0.5 W

WALL MOUNT

VESA®:	200x200mm / 400x400mm ; Screw: M6*8 mm
--------	--

OPERATING CONDITIONS

Temperature:	41°F to 104°F (5°C to 40°C)
Humidity:	20% ~ 80% (non-condensing)

DIMENSIONS

Physical w/ stand:	1081.8 x 663.1 x 329.6 mm
--------------------	---------------------------

WEIGHT

Net w/ stand:	13.39kg
---------------	---------

REGULATIONS

CE, CB, FCC, Energy Star 7.0, BSMI, PSB, RCM

WHAT'S IN THE BOX?

CDE4803 commercial display / Remote Control with batteries / User manual CD wizard / Quick Start Guide / Power Cables / VGA cable / RS232
*Actual content may differ from market to market